

**Motor Clean – modele i specyfikacje**

<b>Model</b>	<b>Pojemność</b>	<b>Wymiary wewn (mm)</b>	<b>Moc ultradźwięków</b>	<b>częstotliwość</b>	<b>moc</b>	<b>Obciążenie pneumatyczne</b>	<b>Wymiary kosza i platformy</b>	<b>System przepływu</b>
<b>MOT-30</b>	30L	550x300x250	600W(1200p-p)	40 kHz	700W	-	500x250x210	-
<b>MOT-50</b>	50L	600x300x300	700W(1500p-p)	40 kHz	700W	-	550x260x225	-
<b>MOT-75</b>	75L	700x350x400	800W(1600p-p)	40 kHz	900W	-	680x330x290	-
<b>MOT-75N</b>	75L	652x420x468	800W(1600p-p)	40 kHz	2250W	30 kg	620x325	V
<b>MOT-150N</b>	150L	700x510x540	1700W(3400p-p)	40 kHz	3500W/3750W	60 kg	670x415	V
<b>MOT-300N</b>	300L	900x650x640	3000W(6000p-p)	40 kHz	7000W	250 kg	850x495	V
<b>MOT-400N</b>	400L	1100x650x690	3400W(6800p-p)	40 kHz	7000W	250 kg	1050x495	V
<b>MOT-600N</b>	600L	1300x800x665	5100W(10200p-p)	40 kHz	9000W	350 kg	1240x636	V
<b>MOT-1000N</b>	1000L	1500x900x860	6800W(13600p-p)	40 kHz	12000W	750 kg	1400x7220	V
<b>MOT-2000N</b>	2000L	1750x1100x1080	10200W(20400p-p)	40 kHz	18000W	1000 kg	1650x910	V
<b>MOT-3000N</b>	3000L	2050x1200x1240	13600W(27200p-p)	40 kHz	24000W	1500 kg	1930x990	V
<b>MOT-4000N</b>	4000L	2400x1500x1260	20400W(40800p-p)	40 kHz	30000W	2000 kg	2340x1320	V
<b>MOT-8000N</b>	8000L	3000x2160x1500	34000W(68000p-p)	40 kHz	60000W		-	V